



Single Phase – 230 Volts AC Code

Baxi 4 kW Geoflo™ System	5119486
Baxi 6 kW Geoflo™ System	5119487
Baxi 8 kW Geoflo™ System	5119488
Baxi 10 kW Geoflo™ System	5119489
Baxi 12 kW Geoflo™ System	5119490
Baxi 16 kW Geoflo™ System	5119491
Baxi 20 kW Geoflo™ System	5119492

Single Phase – 230 Volts; 50 Hz

Thermal Output (kW)	4	6	8	10	12	16	20
Building Size(m ²)	80	120	160	200	240	320	400
Compressors	single	single	single	single	twin	twin	twin
Slinky (quantity)	1	2	2	2	3	4	4
Slinky (length)	40	30	40	50	40	40	50
Antifreeze (25 litre)	1	2	2	3	4	4	5
Power Input	1	1.5	2	2.5	4	4	5
COP 0/55°C	3	3	3	3	3	3	3
COP 0/35°C	4	4	4	4	4	4	4
Power Supply Rating (amps)	16	25	25	25	25	40	50
Max Running Current (amps)	11	14	19	24	28	38	47
Typical Running Current (amps)	4	6	8	10	12	20	24
Typical Starting Current (amps)*	30	50	65	85	54	73	95
Power Supply Size (mm)	2.5	2.5	2.5	2.5	2.5	4	6
Dry Weight (kg)	85	90	95	100	165	167	170
Dimensions (HxWxD)	900x 550x570	900x 550x570	900x 550x570	900x 550x570	900x 900x570	900x 900x570	900x 900x570
Connection Size	28	28	28	28	28	50	50

* Soft start option is available to reduce currents.